



TECHNICAL DATA SHEET

Date 03/06/2010

Description

DIBA is manufactured from high quality reprocessed materials. **DIBA** is produced to stringent performance standards and includes a pronounced emboss to improve mortar adhesion. **DIBA** has good cold flex properties, remaining workable at low temperatures.

Application

DIBA range is suitable for use in vertical and horizontal applications.

Installation

Installation should be in accordance with relevant National Building Regulations. As Building Regulations vary between countries it is the responsibility of the installer to ensure relevant National Building Regulations are fully complied with when installing this damp proof course.

DIBA has good cold flex properties but should not be installed below 5°C. All laps and joints in discontinuous lengths of **DIBA** should be fully lapped by at least 100mm and fully sealed using **DIBAFIX** Double Sided Jointing Tape.

| Characteristic | Units | Value or statement |
|--------------------------|-------------------|--------------------|
| Tensile strength (long) | N/mm ² | 20.0 |
| Tensile strength (trans) | N/mm ² | 11.0 |
| Elongation (long) | % | 300 % |
| Elongation (trans) | % | 275 % |

Storage & Handling

DIBA is classified non-hazardous, and is chemically inert. The product requires no special storage conditions, although measures should be made to keep it clean and dry.

Packings

| Article | Dimensions | Quantity / rol | Quantity rols / palet | Quantity m ² / palet |
|----------|--------------|----------------------|-----------------------|---------------------------------|
| DIBA 10 | 0,10 x 50 m | 5 m ² | 9 x 20 = 180 | 900 m ² |
| DIBA 15 | 0,15 x 50 m | 7,50 m ² | 6 x 20 = 120 | 900 m ² |
| DIBA 20 | 0,20 x 50 m | 10 m ² | 5 x 20 = 100 | 1 000 m ² |
| DIBA 30 | 0,30 x 50 m | 15 m ² | 3 x 20 = 60 | 900 m ² |
| DIBA 36 | 0,365 x 50 m | 18,25 m ² | 3 x 20 = 60 | 1 095 m ² |
| DIBA 40 | 0,40 x 50 m | 20 m ² | 3 x 20 = 60 | 1 200 m ² |
| DIBA 50 | 0,50 x 50 m | 25 m ² | 2 x 20 = 40 | 1 000 m ² |
| DIBA 60 | 0,60 x 50 m | 30 m ² | 2 x 20 = 40 | 1 200 m ² |
| DIBA 80 | 0,80 x 50 m | 40 m ² | 1 x 20 = 20 | 800 m ² |
| DIBA 100 | 1,00 x 50 m | 50 m ² | 1 x 20 = 20 | 1 000 m ² |
| DIBA 120 | 1,20 x 50 m | 60 m ² | 1 x 20 = 20 | 1 200 m ² |



Erich Meyer-Gillessen AG
Rektor-Cremer-Straße, 39
4780 ST. VITH / Emmels - Belgien

Tel. +32 (0)80 / 22 74 80
Fax. +32 (0)80 / 22 63 16
e-mail: info@emg-ag.be